

# LASER CRAFT

## Contour XLR

### Real Remote Offsets

- **Accurate Compass**
- **Wireless Bluetooth Connectivity**
- **Aim, Fire & Shoot**
- **Mapping Made Simple**



**Contour** XLR

# CONTOUR SPECIFICATIONS

<b>SPECIFICATION</b>	<b>CONTOUR XLR</b>	<b>CONTOUR XLRi</b>	<b>CONTOUR XLRic</b>	<b>CONTOUR MAX</b>
<b>WEIGHT</b>	1.36 Kg (3.0 lb.)	1.6 Kg (3.5 lb.)	1.6 Kg (3.5 lb.)	1.59 Kg (3.5 lb.)
<b>DIMENSIONS</b>	18.8 x 10.8 x 25.4 cm (7.4 x 4.25 x 10 in)	18.8 x 10.8 x 26.9 cm (7.4 x 4.25 x 10 in)	18.8 x 10.8 x 26.9 cm (7.4 x 4.25 x 10 in)	18.8 x 10.8 x 25.4 cm (7.4 x 4.25 x 10 in)
<b>ENVIRONMENTAL</b>	Waterproof to IP 67 and NEMA 6	Waterproof to IP 67 and NEMA 6	Waterproof to IP 67 and NEMA 6	Waterproof to IP 67 and NEMA 6
<b>FDA CDRH LASER CLASS</b>	Class I (Eye Safe)	Class I (Eye Safe)	Class I (Eye Safe)	Class I (Eye Safe)
<b>MAXIMUM RANGE</b>	1850 meters (6200 feet)	1850 meters (6200 feet)	1850 meters (6200 feet)	3000 meters (10,000 feet)
<b>RANGE ACCURACY</b>	0.10 meter (0.3 ft) to a white target at 85 m (one sigma)	0.10 meter (0.3 ft) to a white target at 85 m (one sigma)	0.10 meter (0.3 ft) to a white target at 85 m (one sigma)	+/- 1 meters to 1500 meters, +/- 2 meters to 3000 meters
<b>TYPICAL RANGE PERFORMANCE</b>	175 m to overhead cable  400 m to power/telephone poles  400 m to tree (no foliage)  800 m to building or tree (with foliage)	175 m to overhead cable  400 m to power/telephone poles  400 m to tree (no foliage)  800 m to building or tree (with foliage)	175 m to overhead cable  400 m to power/telephone poles  400 m to tree (no foliage)  800 m to building or tree (with foliage)	3 km to white building on bright, clear day  2 km to trees on bright, clear day  (Longer ranges at night and in cloudy conditions)
<b>INCLINATION LIMITS</b>	Not Applicable	360 degrees	+/- 40 degrees	Not Applicable
<b>INCLINATION ACCURACY</b>	Not Applicable	+/- 0.1 degrees (typical)	+/- 0.1 degrees (typical)	Not Applicable
<b>BEARING ACCURACY</b>	Not Applicable	Not Applicable	+/- 0.5 degrees	Not Applicable
<b>POWER SUPPLY (BATTERY)</b>	Internal NiMH pack 9.6V (up to 24 hrs of use)	Internal NiMH pack 9.6V (up to 24 hrs of use)	Internal NiMH pack 9.6V (up to 24 hrs of use)	Internal NiMH pack 9.6V (up to 24 hrs of use)
<b>POWER SUPPLY (CORD) (OPTIONAL)</b>	Cigarette lighter plug (9-18VDC input)	Cigarette lighter plug (9-18VDC input)	Cigarette lighter plug (9-18VDC input)	Cigarette lighter plug (9-18VDC input)

All **Contour** models are equipped with a high power density NiMH Battery Pack, Smart Charger, and a durable, water resistant Hard Case.

All **Contour** units are covered by a one year limited warranty.

All **Contour** units are available in a platform mountable format (**XLR-M Series**) that replaces the handle with a mounting plate and an integral 9-18 VDC power cord.

**NEW** All Contour XLR models are now available with  **Bluetooth™**, please contact your local dealer for more information.

**For more information, contact:**